

Lenses and Visors



Peek Traffic offers a full line of replacement visors and lenses for their vehicle and pedestrian signal products.

Visors

Sheet aluminum and polycarbonate visors are available in several styles for vehicle and pedestrian signals. The cutaway type is standard. Tunnel and full-circle styles reduce or eliminate signal visibility from other approach directions. Full-circle visors have a sharp angular beam cut off for signal installations where highly directional beam characteristics are necessary to prevent driver confusion, such as streets intersecting at a very sharp angle.

All visors have four, slotted mounting tabs for easy attachment to the signal housing door. All visors are flat black on the inside.

Lenses

Round, solid color lenses are Type T prismatic glass or polycarbonate. Round, arrow lenses come standard with a glass lens that has an ITE arrow shield, or in polycarbonate with an ITE arrow on a black field. Glass arrow lenses can be installed with the arrow pointing in any direction.

Polycarbonate arrow lenses cannot be rotated. These lenses have a 1" (25mm) stroke on a black field, and the arrow lenses can be installed pointing up, down, left, or right. The



Walk/Don't/Walk lenses



Cut-away visors

12" WALK and Man legends are Lunar white on a black field, while the DON'T WALK and Hand legends are Portland orange on a black field.

Glass lenses conform to ITE specifications for light transmission, distribution, and chromaticity: Legends are fired on for permanency.

Polycarbonate lenses are vandal resistant and remain unaffected by age and weathering.

One Year Limited Warranty

Peek Traffic warrants these products against manufacturing defects in materials and workmanship for one year from the date of shipment from the factory. Specific contracts and regional laws may alter or vary these terms.

